



# 1/8 MNPT TOGGLE VALVE



## Design Considerations

The Standard Toggle Valve Series promotes a compact, Normally Closed design with multiple configurations to fit the exact end use application. The Toggle Valves are available with Detented or Momentary Handles, and with 2-Way (Non-Exhausting) or 3-Way (Exhausting) 10-32 Female porting. The 3-Way (Exhausting) Toggle Valves relieve air around the handle. The Panel Mount Toggle Valves require a .500 hole and are supplied with two Electroless Nickel Plated Panel Nuts and lock washer.

## Specifications

Body & Panel Nuts: Electroless Nickel Plated Brass  
 Stem: Brass  
 Panel Mounting: 1/2" Panel Hole, 1/4" Max. Thickness  
 Spring: 302 Stainless Steel

Maximum Operating Pressure – 0 - 125 psi  
 Maximum Operating Temperature – -25°F to 180°F  
 Flow Rate – 2.5 SCFM @ 50 psi  
 Toggle Actuation Force – Tested at 50 psi  
 Std Spring, 9 oz. Detented, 1lb 3 oz. Momentary

## Example of How to Order

TA 2 NC-B, 1/8M, 10-32F, B, \* , \*

\* Spring – Std, 50%, HS (Heavy Spring)

\* Port Position – Std, 12:00, 3:00, 9:00

Toggle Color – B – Black, G – Gray, LG – Light Gray, PT – Plated

\* Output Port – 10-32F, 1/16 Barb, 1/8 Barb, 3/32 Barb


Input Port – 1/8 MNPT

Seal Options – B – Buna, E – Ethylene Propylene (EPDM), F – Fluoroelastomer (Viton®)

Normally Closed

2-Way (Non-Exhausting) 3-Way (Exhausting)

TA – Toggle Activated (Detented), TM – Toggle Momentary (Spring Return)



\*\*\* Specify asterisk items only if other than standard